



VIVID ENERGIES

LED Lighting Solutions For Our Future And Your Bottom Line



Type:
Project:
Description:

LED

## Horizontal Floodlight



YM  
Yoke Mount



KM  
Knuckle Mount<sup>1</sup>



UB  
U-Bracket

Up To  
**140**  
Lumens Per Watt

### FEATURES

- Clean design featuring excellent heat dissipation
- IP65 wet location rating
- Instant on with no flicker or hum
- Environmentally friendly containing no mercury

### SPECIFICATIONS

Model Number	Dimensions	CRI	Wattage	Efficacy (LPW)	Mounting Options	Power Factor	Beam Angle (H x V)	Finish Options
VIV-AFL	See page 4 for dimensions	>80	30W 50W 80W 100W 120W	30W - 114 LPW 50W - 125 LPW 80W - 140 LPW 100W - 140 LPW 120W - 140 LPW	Yoke Knuckle <sup>1</sup> U-Bracket	>.9	150° x 110° 150° x 110° 150° x 85° 150° x 85° 150° x 85°	Black Brown

### ORDERING GUIDE

Sample Number: VIV-AFL-80W-UNV-50K-YM-BLK



Vivid: **VIV-FP**

Wattage: **30W, 50W, 80W, 100W, 120W**

Voltage: **UNV** - 120V, 277V

CCT: **30K<sup>3</sup>** - 3000K, **35K<sup>3</sup>** - 3500K, **40K** - 4000K, **50K** - 5000K

Mounting: **YM** - Yoke, **KM<sup>1</sup>** - Knuckle, **UB** - U-Bracket

Finish: **BLK** - Black, **BRN** - Brown

<sup>1,3</sup> Available for 30W and 50W models only



VIVID ENERGIES


LED Lighting Solutions For Our Future And Your Bottom Line




Type:
Project:
Description:

**LED**

**MOUNTING DETAILS**



**KM**  
Knuckle Mount



**YM**  
Yoke Mount



*Not Pictured*  
Similar to yoke but brackets mount on sides of the fixture

**UB**  
U-Bracket

**NOMINAL DIMENSIONS**

Wattage	Mounting	Width	Height	Depth
30W	Yoke	7.25"	7.5"	2"
	Knuckle	7.25"	9.25"	2"
	U-Bracket	7.5"	7"	2"
50W	Yoke	8.5"	8.5"	2"
	Knuckle	8.5"	10.25"	2"
	U-Bracket	8.75"	8"	2"
80W	Yoke	12"	17.75"	4"
100W	U-Bracket	12"	13.25"	4"
120W				

<sup>1,3</sup> Available for 30W and 50W models only